GPE

Gpe Vendors via Toniolo 19/21 - 61032 Fano (PU) - Tel +39 0721.854535 - Fax +39 0721.855200 - www.gpe.it - gpe@gpe.it

technical data sheet **GPE 30**

CONFIGURATIO	N	GPE	E
	Configuration standard and on request.		
SPIRALS			
	In steel; models available on Layout page	MASS	
LIGHTING			
	LED	•	· · ·
GRAPHIC DISPLAY			E.
	Pogrammable in different languages with various spot possibilities, Programmable stand-by.	0000	
CHILLER			
	Compact chiller for quick and easy extraction. Ecological refrigeration Gas R290. Internal Temperature 8°C with external temperature at 32°C. 3°C Version. Optional Quiet Chiller.		
	Programmable Stand-by		
FRONT GLASS		DIMEN	SIONS
	Excellent product visibility	HEIGHT	183 cr
TECHNOLOGY		WIDTH	72 cm 82,5 c
	Telemetry; applicable internet Modem; EVA-DTS, GPE DATA (software updating by PC)	WEIGHT	82,5 C 190 k
PAYMENT SYST	ſFM	ELECTRIC POV ABSORBEI	

PAYMENT SYSTEM

Executive – MDB; predisposed for latest generation payment systems (credit card, Paypal,...)

230V +/- 10% Also possible in 110V version

C

Standard Version Average annual consumption: 1433 KWh 3° Version Average annual consumption: 2270 KWh

m

cm kg